Protek Safe-Top

Lemon FENCING

Protek Safe-Top

Top Profiled Mesh Panel System

The Protek Safe-Top mesh fence system is designed with safety foremost in mind. The top & bottom edges of the fence panel is folded back on itself to remove all potentially sharp edges. This also gives it an aesthetically pleasing appearance, installed so the Safe-Top always faces into site. With 150 x 50mm apertures & welded construction, it is a strong fence option which offers a rigid fence line. Primarily used in school environments or public areas due to its safe design.

Posts, Clips and Fixings

The posts and clips that Alexandra Security Limited offers provide a fixing system which secures the panels but allows for variations. The system is easy to install and allows the panels to be stepped, helping the fence line to follow the contours of the ground. With the vandal resistant security fixings this post and clip system provides a reasonable level of security to any boundary.

Product and Finish Standards

- Mesh panel wire manufactured to BS 4102 and galvanised to BS EN 10244-2:2001 class D, weld strength is 75% of the minimum tensile strength of the wire (tensile range 540-690 N/m2)
- Post material manufactured to BS EN 10210-2:1997 and galvanised to BS EN 10346:2009
- Panels & Posts are powder coated to BS EN 13438:2005 (min 100 micron)

Options

- Plastic or metal clips

Nominal Fence Height (m)	Panel Size Height x Width (mm)	No. Profiles per Panel	Overall Length of Post (mm)	Post Size (mm)	Number of Clips	
					Per Post	Per Corner
0.9	915 x 3,005	2	1,395	60 x 60	3	6
1.2	1,215 x 3,005	2	1,745	60 x 60	3	6
1.5	1,515 x 3,005	2	2,045	60 x 60	4	8
1.8	1,815 x 3,005	2	2,345	60 x 60	4	8

Subject to change

1	Mesh panel - mesh size 150 x 50mm - 5mm wire
2	Post size 60 x 60 SHS
3	Plastic cap - 60 x 60mm
4	M8 x 30 stainless steel security screw
5	Durable Plastic Clip, or can be substituted for a metal clip
6	Folds - Rolled top and bottom 2 per panel

Intermediate post



End post



Internal corner post



External corner post



Suitable For:

School Boundaries, Play Areas, Sports Facilities, Public Parks

15 Year Product Guarantee

Conforms to BS 1722-14:2006