


Protek 1000 & 2000 Bespoke Gates



Hinge Detail



Padlockable Drop Bolt Detail



Suitable For:

see Protek 1000 and 2000 panels on pages 14-19

Protek 1000 & 2000 Bespoke Gates Double Leaf and Single Leaf

Where the customer's project specification requires a particular application, Alexandra is pleased to provide a bespoke manufacture service. Size, colour operation and locks can all be addressed to ensure you are supplied with an entrance solution that matches your requirement exactly. Mesh is secured to framework with clamp bars.


For details on how standard gate construction can be changed to suit a particular application please refer to pages 96-97 for a list of possible options. A range of locks and gate accessories can also be found on pages 98-101.

Product and Finish Standards


- Mesh panel wire manufactured to BS 4102 and galvanised to BS EN 10244-2:2001 class D, weld strength is 75% of the minimum tensile strength of the wire (tensile range 540-690 N/m²)
- Post material manufactured to BS EN 10210-2:1997 and galvanised to BS EN 10346:2009
- Panels & Posts are powder coated to BS EN 13438:2005 (min 100 micron)
- All welding carried out in accordance with BS EN 1011-1 and BS EN 1011-2 by suitable personnel qualified according to BS EN 287-1

Options

- Same gates are available to match the Protek 2000 Privacy panels on pages 18-19
- See Gates Technical section on pages 96-97
- See the range of Gate Accessories on pages 98-101



Padlockable Slide Bolt Detail



Raftering plates to key into concrete foundation

Protek 1000 & 2000
Bespoke Gates