

Protek Safe-Top

Top Profiled Mesh Panel System

The Protek Safe-Top mesh fence system is designed with safety foremost in mind. The top & bottom edges of the fence panel is folded back on itself to remove all potentially sharp edges. This also gives it an aesthetically pleasing appearance, installed so the Safe-Top always faces into site. With 150 x 50mm apertures & welded construction, it is a strong fence option which offers a rigid fence line. Primarily used in school environments or public areas due to its safe design.

Product and Finish Standards

- · Mesh panel wire manufactured to BS 4102 and galvanised to BS EN 10244-2:2001 class D, weld strength is 75% of the minimum tensile strength of the wire (tensile range 540-690 N/m2)
- Post material manufactured to BS EN 10210-2:1997 and galvanised to BS EN 10346:2009
- Panels & Posts are powder coated to BS EN 13438:2005 (min 100 micron)

Posts, Clips and Fixings

The posts and clips that Alexandra Security Limited offers provide a fixing system which secures the panels but allows for variations. The system is easy to install and allows the panels to be stepped, helping the fence line to follow the contours of the ground. With the vandal resistant security fixings this post and clip system provides a reasonable level of security to any boundary.

Options

· Plastic or metal clips



Nominal Fence Height (m)	Panel Size Height x Width (mm)	No. Profiles per Panel	Overall Length of Post (mm)	Post Size (mm)	Number of Clips	
					Per Post	Per Corner
1.2	1,215 x 3,005	2	1,745	60 x 60	3	6
1.00	1,213,131,033	-	1,11,212	001100		Subject to c

- Post size 60 x 60 SHS
- M8 x 30 stainless steel security screw
- Folds Rolled top and bottom 2 per panel





